



Лабораторне обладнання
Реалізація
Ремонт
Модернізація
Виготовлення обладнання за ТЗ замовника



ТОВ ВТП "АСМА-ПРИЛАД"



- Standard configuration as brochure
- Test item **MFR**
- Temperature range 50~400°C
- Temperature accuracy $\pm 0.5^{\circ}\text{C}$
- Power supply AC220V 50Hz

Related Standards:

STANDARDS	GB/T 3682	ISO 1133	ASTM D1238	BS2782
-----------	-----------	----------	---------------	--------

Note: this tester can conform to but not limit to all the standards above, for more standards conformance, please contact us.

Features:

- I Automatically control temperature and cut materials
- I Test item: MFR
- I LCD to display eight pieces of experimental data and average value at most;
- I The temperature can rise up rapidly and to be kept stably

Key Specification:

- I Measuring range 0.1~100g/10min (MFR)
- I Temperature control 100~450°C
- I Temperature accuracy $\leq 0.2^{\circ}\text{C}$
- I Display resolution 0.1°C
- I Display mode LCD
- I Time accuracy 0.01s
- I Cut mode Automatically
- I Accuracy of displacement measurement: $\pm 0.01\text{mm}$ ($\leq 30\text{mm}$)
- I Die diameter: 2.095mm
- I Power supply AC220V 50Hz

Тел./факс: (05236) 7-15-00,
7-08-81, 7-08-83.
Адреса: 27507,
Кіровоградська обл.,
м.Світловодськ,
вул. Чубаря, 33-6

E-mail: info@asma.com.ua
info@asma-pribor.ru
<http://www.asma-pribor.ru>
www.asma-pribor.com
www.asma.com.ua